

Asymptotic standard errors

What are the "Asymptotic Standard Errors"?

The asymptotic standard errors (ASE) are used for analyzing fitting parameter error intervals. For illustration let's start at the best fit parameter set, which can be regarded as a single point in the parameter space. Now we remove the parameter for which we want to calculate the error intervals from this location, that is, we take a single step parallel to its parameter axis. We then calculate the reduced X^2 for this new parameter set. By iterating this procedure we get X^2 as a function of the parameter of interest. The intersection points of this function with a given X^2 confidence limit define the boundaries of the confidence interval of the parameter.

At PQ the asymptotic standard errors are supported by [FluoFit](#) and the [SymPhoTime](#) software.

Advantages and disadvantages

The asymptotic standard errors are a direct outcome of the Marquardt-Levenberg algorithm. They are readily available without any further calculations. On the other hand they are valid if, and only if, the parameters are uncorrelated. A better way of calculating parameter errors are the [support plane analysis](#) or the [bootstrap method](#).

Copyright of this document belongs to PicoQuant GmbH. No parts of it may be reproduced, translated or transferred to third parties without written permission of PicoQuant GmbH. All information given here is reliable to our best knowledge. However, no responsibility is assumed for possible inaccuracies or omissions. Specifications and external appearances are subject to change without notice.



PicoQuant GmbH
Rudower Chaussee 29 (IGZ)
12489 Berlin
Germany

P +49-(0)30-1208820-89
F +49-(0)30-1208820-90
info@picoquant.com
www.picoquant.com